



# The Bulk Conveyor Model US-05

## SPECIFICATIONS:



<b>Type:</b>	Slider bed with 12" wide belt
<b>Main structure:</b>	Aluminum
<b>Trough width:</b>	Bottom 16"
<b>Trough depth:</b>	5" from bottom to top of side panel (7" high side extensions optional)
<b>Length:</b>	Modular system from 10' to 30' in 5' increments
<b>Weight:</b>	225 lbs at 15'. Add 60 lbs per each additional 5' sections
<b>Power:</b>	1hp. 110 volt single phase totally enclosed fan cooled motor
<b>Max amp.draw:</b>	13 Amp. under full load
<b>Transmission:</b>	Single-worm aluminum housing, speed reducer 20:1
<b>Belt:</b>	2-ply, SBR rough top incline 12" wide conveyor belt or PVC smooth belt
<b>Lacing:</b>	Hammer-In Alligator lacing # 7
<b>Belt cleat:</b>	3" high rubber or aluminum cleats (optional)
<b>Belt speed:</b>	100 feet per minute
<b>Wheels:</b>	8" x 2.5" solid rubber tire (Not designed for towing)



### Towing package (Optional)

Consists of one axle trailer with slipper springs, tail/brake lights and safety chains. The draw bar frame is bolted to the conveyor. The draw bar with coupler extends 3 feet in front of conveyor. Draw bar is detachable and should be removed before operating the conveyor.

<b>Trailer weight:</b>	140 lbs.
<b>Draw bar assembly:</b>	50 lbs.
<b>Load capacity:</b>	1100 lbs.
<b>Width:</b>	Fender to fender 55"
<b>Height over ground:</b>	14"
<b>Wheel dimension:</b>	20" pneumatic road tires

**Have questions about the Bulk Conveyor?  
Call and talk to us direct or email us at [sales@liftconveyor.com](mailto:sales@liftconveyor.com)**

**1-800-225-0057**

**[www.liftconveyor.com](http://www.liftconveyor.com)**